



PART	QTY	DESCRIPTION	REV
B2		NOT USED	
C12			
D11		D3 9	
F1			
F1			
F1			
G3			
H4			
H4			
H5			
I2			

- NOTES**
- 1. BOTH CHANNELS SAME EXCEPT FOR WINDING SWITCH; CH. B SHOWN.
 - 2. ALL CAPACITORS IN µF UNLESS SHOWN OTHERWISE.
 - 3. USE DSC REPLACEMENT TRANSISTORS ONLY.
 - 4. HEAVY LINES SHOW MOUNTING POINTS.
 - 5. FOR 235 WPC EXPORT MODE.
 - 6. FOR ULTIMATE VALUES.
 - 7. REPLACE PARTS MARKED Δ AND TP WITH SAME TYPE ONLY FOR CONTINUED SAFETY.
 - 8. CONDUCTOR AND CARRIER: 100% BURN-PROOF.
 - 9. CONNECTION AND DIMENSIONS OF $1/2$ " MOUNTING CHANNEL "B" SHOWN. CHANNEL "A" IN PARENTHESES. (IE K1-A PRODUCTS 1,2,3 BECOME 7,8,3 ON CHANNEL "A", AND C1-B PRODUCTS 7,8,3 BECOME 1,3,3 ON CHANNEL "A").

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION WHICH IS THE PROPERTY OF OSC AUDIO PRODUCTS THAT MAY NOT BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS ELECTRONIC OR MECHANICAL WITHOUT EXPRESS WRITTEN CONSENT FROM OSC AUDIO PRODUCTS